

# PRODUCT DATA SHEET FOR KOVARA 95 SEAM TAPE

## ALKALINITY AND MOISTURE-RESISTANT PRESSURE SENSITIVE TAPE

### PRODUCT DESCRIPTION

KOVARA™ 95 SEAM TAPE is a specially formulated, highly aggressive one-sided pressure-sensitive tape.

### PRODUCT USE

KOVARA™ 95 SEAM TAPE is a 2 in. wide tape used to cover seams between cuts of KOVARA™ 95. It is also used to secure KOVARA™ 95 seams in areas where the membrane has been spliced to fit around floor monuments, columns, or poles.

KOVARA™ 95 SEAM TAPE can be used over concrete slabs with a maximum relative humidity of 95% and maximum pH of 12.

### APPLICATION

Prior to application of KOVARA™ 95 SEAM TAPE, all slab RH testing, pre-installation requirements, concrete substrate preparation, and laying of KOVARA™ 95 should be completed in accordance with the KOVARA™ 95 product page installation guidelines which can be found in our document library: [staticworx.com/brochures-technical-data/](http://staticworx.com/brochures-technical-data/)

Working from one side of the room, lightly butt the pieces of KOVARA™ 95 together and tape all seams with KOVARA™ 95 SEAM TAPE. Maintain adequate tension on the tape when setting to minimize bubbling and wrinkling. Complete by rolling all seams with a hand roller or 75-100 pound resilient roller. NEVER OVERLAP SEAMS as it will potentially telegraph through the finished flooring and NEVER USE COMPRESSION METHOD at any seams.

Sweep the KOVARA™ 95 membrane to remove any installation debris, dust or dirt that may have accumulated during the application. Complete the finished flooring installation in accordance with all manufacturer guidelines.

### KOVARA™ 95 SEAM TAPE DETAILS

Roll Size	1 in. x 180 ft.
Roll Weight	0.6 lb
Packaging	12 rolls / carton

### QUESTIONS/ASSISTANCE

Call StaticWorx Customer Service at 617-923-2000 Monday-Friday between 8:30 am and 5:00 pm EST, or visit us at [www.staticworx.com](http://www.staticworx.com)