






DESCRIPTION			
Total thickness	EN ISO 24346 (EN 428)	mm	6.0
Wearlayer thickness	EN ISO 24340 (EN 429)	mm	2.0
Weight	EN ISO 23997 (EN 430)	lb / ft ²	1.9
Size	EN ISO 24342 (EN 427)	in	25.59 X 25.59
CLASSIFICATION			
Norm / Product specification	-	-	EN ISO 10582 (EN 649)
European classification	EN ISO 10874 (EN 685)	class	34 - 43
Fire rating	EN 13 501-1	class	B _{fl} -s1
Electrical resistance (1)	EN 1081	Ω	$5 \times 10^4 \leq Rt \leq 10^6$
	IEC 61340-4-1		$\leq 10^9$
	IEC 61340-4-5		$\leq 10^9$
	ANSI/ESD STM 7.1		$\leq 10^9$
Static electrical propensity	EN 1815	kV	< 2
	IEC 61340-4-5	V	< 100 (2)
Protection against electrostatic discharges	ESD S20.20	-	OK
	IEC 61340-5-1	-	OK
Slip resistance wet : ramp test with oil	DIN 51130	class	R9
PERFORMANCES			
Wear resistance	EN 660.2	mm ³	≤ 4
Wear group	NF 189	group	P
Type binder content	EN ISO 10582	type	I
Dimensional stability	EN ISO 23999 (EN 434)	%	≤ 0.25
Shore hardness	EN ISO 868	Hd	≥ 90
Castor chair test (type W)	ISO 4918 (EN 425)	-	OK
Thermal conductivity	EN ISO 10456 (EN 12524)	W/(m.K)	0.25
Color fastness	EN 20 105 - B02	degree	≥ 6
Surface treatment	-	-	Evercare™
Chemical product resistance	EN ISO 26987 (EN 423)	class	OK
ENVIRONMENT / INDOOR AIR QUALITY			
TVOC after 28 days	ISO 16000-6	µg/ m ³	< 10
Certification	-	-	Floorscore®
CE MARKING			
	EN 14041	-	  
		-	

(1) Measured before installation

(2) Measured with ESD shoes (type ABEBA and Uvex)