



## EQUIPMENT REQUIRED

1. Dry dust mop
2. Auto-scrubber, low-speed rotary or cylindrical (max 350 RPM)
3. Buffing pads
4. Microfiber wet mop (do not use oil treated mops)

## DAILY MAINTENANCE

Maintenance Type	Equipment Used	Cleaning Products	Cleaning Methods
Manual	<ul style="list-style-type: none"><li>• Dry dust mop</li><li>• Microfiber wet mop</li></ul>	StaticWorx ScrubWorx pH-neutral cleaner	<ol style="list-style-type: none"><li>1. Sweep flooring surface</li><li>2. Wash with mop using ScrubWorx cleaner</li><li>3. Rinse floor with clean water</li></ol>

Maintenance Type	Equipment Used	Cleaning Products	Cleaning Methods
Auto-scrubber	<ul style="list-style-type: none"> <li>Dry dust mop</li> <li>Auto-scrubber</li> <li>StaticWorx gray scrub pads</li> </ul>	StaticWorx ScrubWorx pH-neutral cleaner	<ol style="list-style-type: none"> <li>Sweep flooring surface</li> <li>Scrub using ScrubWorx cleaner</li> <li>Vacuum up solution</li> </ol>

## BIMONTHLY-MONTHLY MAINTENANCE

Maintenance Type	Equipment Used	Cleaning Products	Cleaning Methods
Auto-scrubber	<ul style="list-style-type: none"> <li>Dry dust mop</li> <li>Auto-scrubber</li> <li>StaticWorx gray scrub pads</li> </ul>	StaticWorx ScrubWorx pH-neutral cleaner	<ol style="list-style-type: none"> <li>Sweep flooring surface</li> <li>Scrub using ScrubWorx cleaner</li> <li>Vacuum up solution</li> <li>Rinse floor with clean water</li> </ol>

## INITIAL CLEANING & DEEP CLEANING

Maintenance Type	Equipment Used	Cleaning Products	Cleaning Methods
Auto-scrubber	<ul style="list-style-type: none"> <li>Dry dust mop</li> <li>Auto-scrubber</li> <li>StaticWorx gray scrub pads (for light-moderate soil)</li> <li>StaticWorx maroon scrub pads (for heavy soil and tile restoration)</li> </ul>	StaticWorx ScrubWorx pH-neutral cleaner	<ol style="list-style-type: none"> <li>Sweep flooring surface</li> <li>Scrub using ScrubWorx cleaner</li> <li>Allow solution to sit for 5-10 minutes</li> <li>Repeat step 2</li> <li>Vacuum up solution</li> <li>Rinse floor with clean water</li> </ol>

### NOTES

- These instructions are to be used as a guide and should be adapted to the site conditions and traffic patterns observed in the different areas where GroundLock Extreme tile has been installed.
- In areas where disinfection is required, always rinse with clean water after the application of the disinfectant as per their manufacturer instructions.
- Never use floor cleaners with pH higher than 11.
- Walk-off mats are recommended at the entrance to every room. Clean as needed on a regular basis.
- Use floor mats to prevent scratching from table and chair casters.
- Rubber feet on tables and chairs will stain vinyl floorcoverings. Use non-rubber protectors to prevent stains.
- Never apply any commercial or ESD floor finishes to GroundLock Extreme tile.