

Category	Conductive Rubber Flooring	ESD Solid Vinyl Tile	ESD Epoxy & Urethane	GroundLock Extreme Interlocking Vinyl Tile
Material Cost \$USD from Contractor	High (\$10.00 - \$15.00)	Moderate (\$5.50 - \$6.50)	Lowest (\$4.50 - \$5.50)	High (\$11.50 - \$13.50)
Installation Labor \$USD Cost from Contractor	Moderate (\$2.00 - \$3.00)	Moderate (\$2.00 - \$3.50)	High	Lowest (\$1.50 - \$3.00)
Ease of Installation in Occupied Spaces	Moderate	Moderate	Difficult - Total Shutdown Required	Easiest - Can Be Done Anywhere
Durability	Good - Not Suitable for Fork Trucks	Excellent	Excellent	Excellent
Ease of Repair	Moderate (Can be Repaired with Dry Adhesive)	Easy - Fast Turnover to Use	Difficult - No Traffic for 24 to 72 Hours	Easiest - No Shutdown Needed
Long Term Appearance	Excellent - In Labs and Light Manufacturing	Excellent in All Areas (Buffing Restores to Like New)	Excellent Anywhere - (Micro-abrades Under Chairs)	Excellent Anywhere - Surface Easily Restored
Need for Subfloor Preparation	High (Same as Standard Resilient Flooring)	High (Same as Standard Resilient Flooring)	Highest (Requires Smooth Flat Subfloor)	Lowest
Need to Test for Vapor Emissions	Yes	Yes	Yes	No
Handles/Withstands Rolling Loads	Fair - No Forktrucks	Excellent	Excellent	Excellent
Ease of Rolling	Good	Excellent	Excellent	Excellent
Maintenance	Low - Medium (Sweep, Mop & Buff)	High - Requires Buffing or Wax	Easiest: Sweep and Damp Mop	Sweep & Damp Mop
Meets All Aspects of Standard ANSI/ESD S20.20	Yes	Yes	Yes	Yes
Ease of Finding Small Parts	Easy	Easy	Easiest	Easy
Installation Difficulty	Moderate	Moderate	Difficult - Requires Specialists	Easiest - Can Be DIY
Slip Resistance	> 0.6 (Meets ADA Guidelines)	0.5 - 0.6 (Meets ADA Guidelines)	0.55 - 0.65 (Meets ADA Guidelines)	0.6 (Meets ADA Guidelines)
Chemical Resistance	Superior	Superior	Superior	Superior
Acid, Alkali and Solvent Resistance	Excellent	Good	Excellent	Excellent
Sound Absorption	Excellent (5-19 dB)	4 dB	N/A	N/A
Anti-Fatiguing	Good	No	No	No
PSI	600-850	2500	6000	2500
ASTM 2170 Vapor Limits	Yes	Yes	Yes	No
StaticWorx ESD Warranty	Lifetime	Lifetime	Lifetime	Lifetime
Contributes Towards LEED Credits	Yes	Yes	Yes	Yes
FloorScore or GreenGuard Certified for Air Quality	Yes	Yes	N/A	Yes
Recommended Applications	Light Manufacturing, Labs, R&D, Cleanrooms	All Applications	All Applications	All Applications
Can Be Installed Over Old Floors	Yes	Yes	No	Yes