staticworx.com

CoatZF is the only low VOC coating of its

Bag-in-a-box packaging.

kind on the market. • 0% VOC per Title 17, California Code

damage! Our gusseted, form-fit multi-ply bag

- of Regulations, Division 3, Chapter 1,
- Meets or exceeds the VOC guidelines of U.S. EPA. OTC and CARB.

Low static generation on any surface.

- <.1kV (100 volts) ANSI/STM 97.2 and</p>
- Meets or exceeds stringent requirements of ANSI/ESD S20.20 for charge generation on

P.O. Box 1556, Williston, VT 05495 t: 617.923.2000 f: 617.467.5871

- Your floor will measure <1.0 X 10 E9.
- 5. Only clean your floor with Staticworx Triboshield cleaner.

CoatZF can be applied to many surfaces:

- Concrete
- Epoxy coatings
- Polyurethane Sealers
- VCT, SVT, SDT
- Any ESD tile

CoatZF does not contain harmful chemicals:

- NO APE (alkylphenol ethoxylates) surfactants
- NO Carcinogens, Mutagens, or Reproductive Toxins
- NO Ozone-depleting compounds
- NO Ammonia
- NO Heavy metals (Zinc Free, Lead Free RoHS Compliant)
- NO Flammable components
- NO Components toxic to aquatic life

Convert any hard surface floor into a static control floor.

ZINC-FREE ADVANCED STATIC CONTROL

Got vinyl tile? Maybe sealed concrete? Infuse static control properties and make your floor ESD compliant.*

Budget-friendly, easy 5-Step Static Killer Program.

StaticWOrX

COATZF

FLOOR POLISH

grounded solution

- 1. Remove any waxes or polishes from your old floor.
- 2. Apply 2 coats of CoatZF per our instructions.
- 3. Measure your floor with our ANSI/ESD S7.1 megohm meter:
- 4. Test several high traffic areas every 2 weeks.







