

LEED INFORMATION FOR AMERIWORX ESD VINYL TILE

LEED™ V4 SPECIFICATION PUBLISHER

IEQ Credit 4.3 — *Low-emitting Materials: Flooring Systems*

Option 2 under this credit in the LEED 2009 component of LEED v3 accepts all flooring elements meeting the requirements of the CA Department of Health Services Standard Practice for the testing of Volatile Organic Emissions from Various Sources Using Small-Scale Environmental Chambers. Ameriworx tile achieved a zero detectable VOC result in this test (CA DHS 01360).

IEQ Credit 4.1 — *Low-emitting Materials: Adhesives and Sealants*

Vinyl tile adhesives must have a VOC limit of 50 g/l. Statbond conductive adhesive meets this requirement at <0.1g/l VOC's.

MR Credits 4.1, 4.2 — *Recycled Content: (post-consumer + 1/2 pre-consumer)*

Pre-consumer recycled content: 10.4%

Post-consumer recycled content: 0%

Since credit is given for only 1/2 of the pre-consumer content, our total recycled content per MR Credits 4.1 and 4.2 is 5.2%. Per this Credit, the sum of the recycled content of all the project materials must equal at least 10% (4.1) or 20% (4.2) to obtain the credit.

MR Credits 5.1, 5.2 — *Regional Materials: Extracted, Harvested & Manufactured Regionally*

Origin: Calhoun, GA. Per this credit, regional materials must constitute at least 10% (5.1) or 20% (5.2) of all the project materials to obtain the credit.